



HELICOPTER LANDING AREA CERTIFICATE

CPC-1

The above-named helideck has been inspected in accordance with CAP 437, BSL D 5-1, and HCA requirements for Offshore Helidecks.

The helideck has been found suitable for helicopter operations subject to:

1. Such non-compliances and restrictions as may be listed below; and,
2. Authorization by the helicopter operator.

Wind (T°)	Kts	Limitation /Comment
<ul style="list-style-type: none"> • 045-135 • 045-135 • 045-135 • 135-160 • 060-100 • 010-060 	<ul style="list-style-type: none"> • 0-20 • 21-30 • 31 plus • 21 plus All 	Manned platform <ul style="list-style-type: none"> • Use zero wind for performance calculations • Extreme caution due to possible turbulence • Emergency only • Extreme caution due to possible turbulence • Main generators running without head recovery add 12 to ambient temperature for performance calculations • CPC-1 helideck closed when wind is above 7kts and flare is unlit. No restriction when topside is depressurised (Assume topside pressurised unless advised) • Aircraft hanger - may cause turbulence • Table 1 (T) if overflight of 5:1 infringements unavoidable • Maximum single pax weight of 160kg due to inbound pax scale weight range

	Non-Compliance
150°	Refuelling unit marginal infringement in second sector of LOS
5:1	North & south access platforms 4m from SLA
Misc	Inboard perimeter lights are not co-incident with perimeter line Callsign CPC-1

Valid for helicopters with: Maximum 'D' value:	'D' = 22.2m
Maximum take-off weight:	't' = 12.6t
This certification shall remain in force until (unless previously revoked or suspended)	10th January 2025

Notes:

1. This certificate is non-transferable.
2. The certificate holder is responsible for ensuring that the helideck, its environs and related equipment are at all times fit for purpose and that the helideck crew are suitably qualified, equipped and trained in the exercise of their duties.
3. This certificate shall cease to be valid if:
 - ◆ Changes of ownership or name of installation/vessel are made without notification to the HCA.
 - ◆ Changes to the helideck, its environs and/or related equipment are made without prior agreement of the HCA.
 - ◆ Levels of Helideck crew qualifications/competency are not maintained to the levels described in the OEUK Guidelines for Management of Offshore Helidecks or suitable alternative standards.
4. Any proposed changes are to be accompanied by drawings in plan and elevation with photographs where possible, particularly when such changes concern:
 - ◆ Modification to installation/vessel physical characteristics within the 150°, 210° and 180° falling gradient obstacle protected surfaces; and/or structural modifications to other areas of the installation/vessel that may affect or alter the airflow or turbulence experienced over the helideck
5. The Norwegian 1.25D requirement is only relevant to vessels constructed (keel laid) after 1 January 2008.


 David Rae
Helideck Certification Agency

Date: 11th October 2024