



# HELICOPTER LANDING AREA CERTIFICATE

## Edda Flora

The above-named helideck has been inspected in accordance with CAP 437, BSL D 5-1, and HCA requirements for Offshore Helidecks.

The helideck has been found suitable for helicopter operations subject to:

1. Such non-compliances and restrictions as may be listed below; and,
2. Authorization by the helicopter operator.

| Wind (T°) | Kts | Limitation /Comment  |
|-----------|-----|--|
|           |     | MSV<br>• CAT 3 Bow Helideck – Day Ops only when vessel into wind<br>• Daylight operations only (UK waters & UK reg aircraft)<br>• DIFFS fitted - no landing net outside Norway.<br>• HMS Rev.9B + Lights fitted<br>• Friction test valid to 06.03.2026.<br>• Helideck landing net to be fitted during flight operations in Norway. |

|      | Non-Compliance   |
|------|--|
| 210° | Parts of the foldable perimeter net hydraulic pipelines 6cm ADL with connectors 14cm ADL, 25cm inside line at maximum<br>Helideck net tie down points are 7cm ADL 20cm inside white line.<br>Mast for nav light 3.4m SLA and 4.1m AD (temporary obstruction) - covered by procedures to remove before flight operations. |
| Misc | Circle and H lights not fitted<br>Norway only: Dual agent not fitted.  |

|   |   |
|---|---|
| Valid for helicopters with:<br>Maximum 'D' value:                                       | 'D' = 20.88m (Norway 1.25D - Dh = 20,88m / Keel laid pre 2008 ) |
| Maximum take-off weight:  | 't' = 12.8t   |
| This certification shall remain in force until (unless previously revoked or suspended) | 25 February 2026  |

### Notes:

1. This certificate is non-transferable.
2. The certificate holder is responsible for ensuring that the helideck, its environs and related equipment are at all times fit for purpose and that the helideck crew are suitably qualified, equipped and trained in the exercise of their duties.
3. This certificate shall cease to be valid if:
  - ◆ Changes of ownership or name of installation/vessel are made without notification to the HCA.
  - ◆ Changes to the helideck, its environs and/or related equipment are made without prior agreement of the HCA.
  - ◆ Levels of Helideck crew qualifications/competency are not maintained to the levels described in the OEUK Guidelines for Management of Offshore Helidecks or suitable alternative standards.
4. Any proposed changes are to be accompanied by drawings in plan and elevation with photographs where possible, particularly when such changes concern:
  - ◆ Modification to installation/vessel physical characteristics within the 150°, 210° and 180° falling gradient obstacle protected surfaces; and/or structural modifications to other areas of the installation/vessel that may affect or alter the airflow or turbulence experienced over the helideck
5. The Norwegian 1.25D requirement is only relevant to vessels constructed (keel laid) after 1 January 2008.

David Rae  
Helideck Certification Agency

Date: 25 March 2024