



HELICOPTER LANDING AREA CERTIFICATE

FRIDA I

The above named helideck has been inspected in accordance with CAP 437, BSL D 5-1, and HCA requirements for Offshore Helidecks.

The helideck has been found suitable for helicopter operations subject to:

1. Such non-compliances and restrictions as may be listed below; and,
2. Authorisation by the helicopter operator.

Wind (T°)	Kts	Limitation /Comment
	<30 knots	Semi Sub •Daylight operations only - no Circle/H lighting •No automated cloud, visibility, or present weather sensors - mandatory radar approach •Table 1(T&L) if overflight of 5:1 infringements is unavoidable

		Non Compliance
5:1		•Outer edge of perimeter net 2.2m from outer edge of perimeter line •Foam monitor / Access platforms, & fwd lifeboat stn infringe sector
Misc		No ground power unit - no planned shutdowns Approved high friction surface - net may not be present No DG to be shipped by air

Valid for helicopters with: Maximum 'D' value:	'D' = 22.2 (Norway 1.25D - 'D' = N/A)
Maximum take-off weight:	't' = 12.8
This certification shall remain in force until (unless previously revoked or suspended)	03 November 2021

Notes:

1. This certificate is non-transferable.
2. The certificate holder is responsible for ensuring that the helideck, its environs and related equipment are at all times fit for purpose and that the helideck crew are suitably qualified, equipped and trained in the exercise of their duties.
3. This certificate shall cease to be valid if:
 - ◆ Changes of ownership or name of installation/vessel are made without notification to the HCA.
 - ◆ Changes to the helideck, its environs and/or related equipment are made without prior agreement of the HCA.
 - ◆ Levels of Helideck crew qualifications/competency are not maintained to the levels described in the UKOOA Guidelines for Management of Offshore Helidecks or suitable alternative standards.
 - ◆ Vessel has been laid-up for longer than 180 days.
4. Any proposed changes are to be accompanied by drawings in plan and elevation with photographs where possible, particularly when such changes concern:
 - ◆ Modification to installation/vessel physical characteristics within the 150°, 210° and 180° falling gradient obstacle protected surfaces; and/or structural modifications to other areas of the installation/vessel that may affect or alter the airflow or turbulence experienced over the helideck
5. The Norwegian 1.25D requirement is only relevant to vessels constructed (keel laid) after 1 January 2008.

Alex Knight
Helideck Certification Agency

Date: 15 May 2020