



# HELICOPTER LANDING AREA CERTIFICATE

## Lennox

The above-named helideck has been inspected in accordance with CAP 437, BSL D 5-1, and HCA requirements for Offshore Helidecks.

The helideck has been found suitable for helicopter operations subject to:

1. Such non-compliances and restrictions as may be listed below; and,
2. Authorization by the helicopter operator.

Wind (T°)	Kts	Limitation /Comment
		NUI - Manually operated foam monitors installed • Table 1(T) if overflight of 5:1 items is unavoidable • Approved Friction Surface - No net

	Non-Compliance
210°	Outside edge of perimeter net frame 250mm adl rising to 340mm adl Vent boom marginally infringes sector
5:1	SW access platform and microwave dish
Misc	Height limitation in 210 OFS & 1st sector of LOS is 150mm Deck closed when Jack-up alongside

Valid for helicopters with: Maximum 'D' value:	'D' = 14.65m
Maximum take-off weight:	't' = 4.9t
This certification shall remain in force until (unless previously revoked or suspended)	8 <sup>th</sup> November 2024

### Notes:

1. This certificate is non-transferable.
2. The certificate holder is responsible for ensuring that the helideck, its environs and related equipment are at all times fit for purpose and that the helideck crew are suitably qualified, equipped and trained in the exercise of their duties.
3. This certificate shall cease to be valid if:
  - ◆ Changes of ownership or name of installation/vessel are made without notification to the HCA.
  - ◆ Changes to the helideck, its environs and/or related equipment are made without prior agreement of the HCA.
  - ◆ Levels of Helideck crew qualifications/competency are not maintained to the levels described in the OEUK Guidelines for Management of Offshore Helidecks or suitable alternative standards.
4. Any proposed changes are to be accompanied by drawings in plan and elevation with photographs where possible, particularly when such changes concern:
  - ◆ Modification to installation/vessel physical characteristics within the 150°, 210° and 180° falling gradient obstacle protected surfaces; and/or structural modifications to other areas of the installation/vessel that may affect or alter the airflow or turbulence experienced over the helideck
5. The Norwegian 1.25D requirement is only relevant to vessels constructed (keel laid) after 1 January 2008.

David Rae

Date: 14<sup>th</sup> July 2023