



# HELIDECK INFORMATION PLATE

HELIDECK Elev <b>Check</b>	VAR <b>Check</b>	POSITION <b>Check</b>	<b>Noble Houston Colbert</b>		
HEIGHT OF INSTALLATION: HIGHEST OBSTACLE WITHIN 5NM:		<b>315 ft</b> <b>Check</b>	VHF <b>Check</b>	NDB <b>Nil</b>	Issue Date <b>21 April 2023</b>
FUELLING INSTALLATION: STARTING EQUIPMENT:		<b>Yes</b> <b>Yes</b>	Operating Company		Issued By
(Dh Norway = 18.24m / SLA 22.8m) HELIDECK D value: <b>22.8m</b> P/R/H Category: 1 Max Weight: <b>14.6</b> Circle & H Lights: Fitted			<b>Noble Drilling</b>		<b>Helideck Certification Agency</b>



Wind (T°)	Kts	Limitation /Comment
		<b>Jack (MODU)</b> • Stable deck criteria apply for operations whilst under tow ie. Pitch & Roll maximum 1°, Heave 2m. • Mandatory ARA required for all operations
		<b>Non Compliance</b>
	Misc	Comprehensive Meteorological & electronic pitch, roll and heave measuring equipment not available on site. No fuel system available