



HELICOPTER LANDING AREA CERTIFICATE

Oceanic Champion

The above-named helideck has been inspected in accordance with CAP 437, BSL D 5-1, and HCA requirements for Offshore Helidecks.

The helideck has been found suitable for helicopter operations subject to:

1. Such non-compliances and restrictions as may be listed below; and,
2. Authorization by the helicopter operator.

| Wind (T°) | Kts | Limitation /Comment |
|-----------|--------|---|
| | +30Kts | Seismic Vessel - Amidships helideck • Daylight operations only - UK Waters and UK reg Aircraft • No helicopter operations unless net fitted - insufficient friction. • Friction test valid to 27th July 2023 - average score 0.59mu. • Table 1(T) to be applied if overflight of aft deck unavoidable • Seismic arrays deployed - Table 1(T&L) regardless of overflight Stowed - Table 1(T) • Offset aiming circle due to LOS obstruction • HMS rev 8c -Stable deck conditions apply. |

| | Non-Compliance |
|------|--|
| 210° | Norway only - handrails 250mm ADL at access platforms. |
| 150° | Mast with red warning light at Sat dome marginally protrudes LOS. Aft of helideck, port side: 6.4m from SLA - 5.0m ADL. |
| 5:1 | Main deck aft of helideck. Seismic booms & cable arrays (when deployed) |
| Misc | HMS repeater lights not fitted. Circle and H lights not fitted. Dual Agent not fitted - Norway only. |

| | |
|---|---|
| Valid for helicopters with: Maximum 'D' value: | 'D' = 22.2m (Norway 1.25D - 'Dh' = 22,2m (Keel laid 2007) |
| Maximum take-off weight: | 't' = 12.8t |
| This certification shall remain in force until (unless previously revoked or suspended) | 15 th March 2025 |

Notes:

1. This certificate is non-transferable.
2. The certificate holder is responsible for ensuring that the helideck, its environs and related equipment are at all times fit for purpose and that the helideck crew are suitably qualified, equipped and trained in the exercise of their duties.
3. This certificate shall cease to be valid if:
 - ◆ Changes of ownership or name of installation/vessel are made without notification to the HCA.
 - ◆ Changes to the helideck, its environs and/or related equipment are made without prior agreement of the HCA.
 - ◆ Levels of Helideck crew qualifications/competency are not maintained to the levels described in the OEUK Guidelines for Management of Offshore Helidecks or suitable alternative standards.
4. Any proposed changes are to be accompanied by drawings in plan and elevation with photographs where possible, particularly when such changes concern:
 - ◆ Modification to installation/vessel physical characteristics within the 150°, 210° and 180° falling gradient obstacle protected surfaces; and/or structural modifications to other areas of the installation/vessel that may affect or alter the airflow or turbulence experienced over the helideck
5. The Norwegian 1.25D requirement is only relevant to vessels constructed (keel laid) after 1 January 2008.

David Rae
Helideck Certification Agency

Date: 22 May 2023