



# HELIDECK INFORMATION PLATE

HELIDECK Elev. <b>116 ft</b>	VAR <b>Check</b>	POSITION <b>Check</b>	<b>XSZP</b> <b>Safe Zephyrus</b>		
HEIGHT OF INSTALLATION: <b>287</b>		VHF <b>Check</b>	NDB <b>570</b> <b>SZE</b>	Issue Date <b>09 February</b> <b>2022</b>	
HIGHEST OBSTACLE WITHIN 5NM: <b>Check</b>		Operating Company		Issued By	
FUELLING INSTALLATION: <b>Yes</b>		<b>Prosafe</b>		<b>Helideck</b> <b>Certification</b> <b>Agency</b>	
STARTING EQUIPMENT: <b>Yes</b>					
Norway 1.25D - 'DH' = <b>22.2 / SLA27.75</b>					
HELIDECK D value: <b>22.2m</b>					
P/R/H Category: <b>1</b>					
Max Weight: <b>13.0t</b>					
Circle & H Lights: <b>Yes</b>					



Wind (T°)	Kts	Limitation /Comment
		Semi-Sub - Flotel <ul style="list-style-type: none"> <li>• Table 1(T) if overflight of forward port access platform unavoidable</li> <li>• Approved friction surface - no net</li> <li>• DIFFS Fitted</li> <li>• HMS Rev.9B with Repeater lights fitted.</li> </ul>
		<b>Non-Compliance</b>
	Sig 5:1	Forward port access platform 6m from SLA