



# HELIDECK INFORMATION PLATE

HELIDECK Elev <b>35</b> ft	VAR Check	POSITION Mobile	<b>Vantage</b>		
HEIGHT OF INSTALLATION: <b>113</b>		VHF	NDB <b>410</b> <b>LMHY3</b>	Issue Date <b>21 Jan 2020</b>	
HIGHEST OBSTACLE WITHIN 5NM:		Operating Company		Issued By	
FUELLING INSTALLATION: <b>No</b>		<b>Eidesvik</b>		<b>Helideck Certification Agency</b>	
STARTING EQUIPMENT: <b>No</b>					
HELIDECK D value: <b>22.2</b>					
P/R/H Category: <b>2</b>					
Max Weight: <b>12.8</b>					



Wind (T°)	Kts	Limitation /Comment
		<b>Seismic Vessel</b> • Daylight operations only. Circle & "H" lights not fitted • Table 1(T) if overflight of 5:1 obstructions unavoidable • Seismic arrays: deployed - Table 1(T & L) regardless of overflight stowed - no limitation Whenever practical, avoid or minimize overflight of arrays
		<b>Non Compliance</b>
	150°	Hand-rails at access points and mid-point on walkway forward are marginal infrinements in second sector of LOS
	5:1	Main deck forward corners on port and starboard sides Cable arrays (when deployed)